



# North American Pipe Corporation™

## ASTM D2949: Schedule 30 Thin Wall Pipe

North American Pipe's ASTM D2949 Schedule 30 Thin Wall DWV product line is manufactured to meet the needs for commercial and residential piping systems. With top quality raw materials and modern processing technology, North American Pipe's ASTM D2949 Schedule 30 Thin Wall DWV pipe meets all industry standards in addition to our own rigorous quality control standards. Whether specifying or installing our products, you can be assured that North American Pipe will provide the pipe "Right, On Time, All the Time".



### Short Form Specification ASTM D2949 Schedule 30 Thin Wall Pipe

<b>Pipe Standard:</b>	ASTM D2949
<b>Pipe Compound:</b>	ASTM D1784 Cell Class 112454
<b>End Type:</b>	Plain
<b>Certifications:</b>	ANSI/NSF Standard 14
<b>Applications:</b>	Residential Drain, Waste & Vent
<b>Color:</b>	White
<b>Lay Length:</b>	10'
<b>Installation:</b>	North American Pipe's Installation Guide for Solvent Welded PVC Pipe

Rev: 04/2012



# North American Pipe Corporation™

## ASTM D2949: Schedule 30 Thin Wall Pipe



NOMINAL PIPE SIZE	OUTSIDE DIA. – NOM. (OD)	(T)
3"	3.25	.125

When joining 3.25" outside diameter PVC DWV piping to 3" Schedule 40 PVC DWV piping, it is necessary to use either reducer bushings or increasers as show in ASTM D2949.

Note: These dimensions are for estimating purposes only